

**0520 6 sided Multi-Lok
082-6200**



Dimensions	mm	(inch)
Height	203	(7.99)
Width	230	(9.06)
Swing Diameter	235	(9.25)

Weight	kg	(lbs)
	20	(44)

Maximum Holding Capacity	mm	(inch)
Dual Station 12 - Workholding Stations	85	(3.35)
Single Station 6 - Workholding Stations	185	(7.28)

**Maximum Recommended
Torque Clamping Force**

2,520 lbs. @ 14 ft-lbs.
(11.2 kN @ 19 N-m)

**1030 6 sided Multi-Lok
5ML1030-61**



Dimensions	mm	(inch)
Height	305	(12.01)
Width	300	(11.81)
Swing Diameter	316	(12.44)

Weight	kg	(lbs)
	58	(128)

Maximum Holding Capacity	mm	(inch)
Dual Station 12 - Workholding Stations	130	(5.12)
Single Station 6 - Workholding Stations	280	(11.02)

**Maximum Recommended
Torque Clamping Force**

5,000 lbs. @ 52 ft-lbs.
(22.0 kN @ 70 N-m)

**1540 6 sided Multi-Lok
5ML1540-61**



Dimensions	mm	(inch)
Height	407	(16.02)
Width	410	(16.14)
Swing Diameter	436	(17.17)

Weight	kg	(lbs)
	138	(304)

Maximum Holding Capacity	mm	(inch)
Dual Station 12 - Workholding Stations	175	(6.89)
Single Station 6 - Workholding Stations	380	(14.96)

**Maximum Recommended
Torque Clamping Force**

9,000 lbs. @ 118 ft-lbs.
(40.0 kN @ 160 N-m)

**0525 6 sided Multi-Lok
082-6201**



Dimensions	mm	(inch)
Height	253	(9.96)
Width	230	(9.06)
Swing Diameter	235	(9.25)

Weight	kg	(lbs)
	23	(51)

Maximum Holding Capacity	mm	(inch)
Dual Station 12 - Workholding Stations	110	(4.33)
Single Station 6 - Workholding Stations	235	(9.25)

**Maximum Recommended
Torque Clamping Force**

2,520 lbs. @ 14 ft-lbs.
(11.2 kN @ 19 N-m)

**1040 6 sided Multi-Lok
5ML1040-61**



Dimensions	mm	(inch)
Height	405	(15.94)
Width	300	(11.81)
Swing Diameter	316	(12.44)

Weight	kg	(lbs)
	75	(165)

Maximum Holding Capacity	mm	(inch)
Dual Station 12 - Workholding Stations	180	(7.09)
Single Station 6 - Workholding Stations	380	(14.96)

**Maximum Recommended
Torque Clamping Force**

5,000 lbs. @ 52 ft-lbs.
(22.0 kN @ 70 N-m)

**1550 6 sided Multi-Lok
5ML1550-61**



Dimensions	mm	(inch)
Height	507	(19.96)
Width	410	(16.14)
Swing Diameter	436	(17.17)

Weight	kg	(lbs)
	162	(356)

Maximum Holding Capacity	mm	(inch)
Dual Station 12 - Workholding Stations	225	(8.86)
Single Station 6 - Workholding Stations	480	(18.90)

**Maximum Recommended
Torque Clamping Force**

9,000 lbs. @ 118 ft-lbs.
(40.0 kN @ 160 N-m)