0520 Qwik-Lok 081-1200



Dimensions Height Width Length	mm 75 50 203	(inch) (2.95) (1.97) (7.99)
Weight	kg 2	(lbs) (5)
Maximum Holding Capacity	mm	(inch)
Dual Station 2 - Workholding Stations	85	(3.35)
Single Station 1 - Workholding Station	185	(7.28)

Maximum Recommended Torque Clamping Force

2,520 lbs. @ 14 ft-lbs. (11.2 kN @ 19 N-m)

1030 Qwik-Lok 5QL1030-AL



Dimensions	mm	(inch)
Height	95	(3.74)
Width	100	(3.94)
Length	305	(12.01)
Weight	kg 9	(lbs) (19)
Maximum Holding Capacity	mm	(inch)
Dual Station 2 - Workholding Stations	130 s	(5.12)
Single Station 1 - Workholding Station	280	(11.02)

Maximum Recommended Torque Clamping Force

5,000 lbs. @ 52 ft-lbs. (22.0 kN @ 70 N-m)

1540 Qwik-Lok 5QL1540-AL



Dimensions	mm	(inch)
Height	120	(4.72)
Width	150	(5.91)
Length	407	(16.02)
Weight	kg	(lbs)
	21	(46)
Maximum		
Holding Capacity	mm	(inch)
Dual Station 2 - Total Workholding	175 Stations	(6.89)
Single Station 1 - Workholding Statio		(14.96)

Maximum Recommended Torque Clamping Force

9,000 lbs. @ 118 ft-lbs. (40.0 kN @ 160 N-m)

0525 Qwik-Lok 081-1205



(inch)

mm

Dimensions

Height	/5	(2.95)
Width	50	(1.97)
Length	253	(9.96)
Weight	kg	(lbs)
	3	(6)
Maximum		
Holding Capacity	mm	(inch)
Dual Station 2 - Workholding Statio	110 ons	(4.33)
Single Station 1 - Workholding Statio	235	(9.25)

Maximum Recommended Torque Clamping Force

2,520 lbs. @ 14 ft-lbs. (11.2 kN @ 19 N-m)

1040 Qwik-Lok Aluminum Base 5QL1040-AL Cast Iron Base 5QL1040-CI



Dimensions	mm	(inch)
Height	95	(3.74)
Width	100	(3.94)
Length	405	(15.94)
Weight	kg	(lbs)
Aluminum Base	11	(24)
Cast Iron Base	18	(39)
Maximum		
Holding Capacity	mm	(inch)
Dual Station 2 - Workholding Stations	180 s	(7.09)
Single Station 1 - Workholding Station	380	(14.96)

Maximum Recommended Torque Clamping Force

5,000 lbs. @ 52 ft-lbs. (22.0 kN @ 70 N-m)

1550 Qwik-Lok Aluminum Base 5QL1550-AL Cast Iron Base 5QL1550-Cl



mm	(inch)
120	(4.72)
150	(5.91)
507	(19.96)
kg	(lbs)
24	(54)
41	(89)
mm	(inch)
225 ns	(8.86)
480 n	(18.90)
	120 150 507 kg 24 41 mm 225

QwikChange™ Accessories Pages 22-31 Mounting Accessories
Pages 34-35

Torque Clamping Force

9,000 lbs. @ 118 Ft-lbs.

(40.0 kN @ 160 N-m)

9