



Segments For Master Plates — Style O

Made with 6061 T-6 condition aluminum or 319 cast aluminum

Dimensions in millimeters unless otherwise noted • Weights in kgs. • Custom configurations available

PLATE SIZE	ALUMINUM PART#	A OUTSIDE DIAMETER	B INSIDE DIAMETER	C HEIGHT	WEIGHT	
381+	10SP2	254.0	N/A	50.8	7.0	
	10SP4	254.0	N/A	101.6	13.9	
	10SP6	254.0	N/A	152.4	21.4	
	10SP8	254.0	N/A	203.2	28.9	
	111SP2.5	279.4	25.4	63.5	10.5	
	121SP2.5	304.8	25.4	63.5	12.7	
	131SP2.5	330.2	25.4	63.5	14.9	
	144SP3	355.6	101.6	76.2	19.2	
	145SP3	355.6	127.0	76.2	18.3	
	157SP2	381.0	177.8	50.8	12.5	
	157SP4	381.0	177.8	101.6	25.2	
	157SP6	381.0	177.8	152.4	38.3	
	159SP2	381.0	228.6	50.8	10.2	
	159SP4	381.0	228.6	101.6	20.7	
	161SP4	406.4	25.4	101.6	36.7	
167SP3	406.4	177.8	76.2	22.2		
457+	1812SP2	457.2	304.8	50.8	12.4	
	1812SP4	457.2	304.8	101.6	25.4	
	1812SP6	457.2	304.8	152.4	38.5	
	199SP3	482.6	228.6	76.2	29.7	
	2112SP2	533.4	304.8	50.8	21.0	
	2112SP4	533.4	304.8	101.6	42.3	
	2210SP2	558.8	254.0	50.8	27.2	
	2210SP3	558.8	254.0	76.2	41.0	
533+	2216SP2	558.8	406.4	50.8	16.1	
	2216SP4	558.8	406.4	101.6	32.5	
610+	2415SP2	609.6	381.0	50.8	25.0	
	2415SP4	609.6	381.0	101.6	50.2	
	2418SP2	609.6	457.2	50.8	17.9	
	2418SP4	609.6	457.2	101.6	36.0	
	2418SP6	609.6	457.2	152.4	54.5	
	2618SP2	660.4	457.2	50.8	25.1	
	2618SP4	660.4	457.2	101.6	50.5	
	2618SP6	660.4	457.2	152.4	76.4	
	3015SP4	762.0	381.0	101.6	97.1	
	762+	3024SP2	762.0	609.6	50.8	23.0
3024SP4		762.0	609.6	101.6	46.6	
3024SP6		762.0	609.6	152.4	70.8	
3226SP4		812.8	660.4	101.6	50.2	
914+	3628SP4	914.4	711.2	101.6	73.9	
	3628SP6	914.4	711.2	152.4	112.0	
	3630SP2	914.4	762.0	50.8	28.4	
	3630SP4	914.4	762.0	101.6	57.3	
	3830SP4	965.2	762.0	101.6	78.7	
	4030SP2	1016.0	762.0	50.8	50.3	
	4030SP4	1016.0	762.0	101.6	101.2	
	1219+	4032SP4	1016.0	812.8	101.6	83.3
4232SP4		1066.8	812.8	101.6	107.0	
4236SP2		1066.8	914.4	50.8	33.5	
4236SP4		1066.8	914.4	101.6	67.9	
4434SP2		1117.6	863.6	50.8	56.0	
4434SP4		1117.6	863.6	101.6	112.9	
4838SP2		1219.2	965.2	50.8	61.9	
4842SP2		1219.2	1066.8	50.8	38.9	
4842SP4		1219.2	1066.8	101.6	88.5	
5040SP2		1270.0	1016.0	50.8	64.8	
5040SP4		1270.0	1016.0	101.6	130.5	
5440SP2		1371.6	1016.0	50.8	94.8	
1524		6050SP2	1524.0	1270.0	50.8	79.4