

REPLACEMENT SWIVEL SHOES



Shoes #2 & #3 give you a larger clamping surface. Shoes #4 & #5 are for holding round workpieces.

Part Number	Model
25518	#2
25520	#3
25522	#4
25524	#5
25530	Set of all 4

For the complete line of Mono-Bloc style clamps, see our website:
MiteeBite.com

DELUXE MONO-BLOC START-UP KIT



Kit includes: (2) standard-duty Mono-Bloc Clamps with 2 5/8" arm, (2) standard-duty Riser Blocks,

- (1) Extension Arm,
- (1) standard-duty T-Wrench,
- (2) M10x35mm screws,
- (2) M10x40mm screws,
- (2) T-nuts (choose from chart at right)

Part Number	T-Slot Size
25725	1/2
25727	9/16
25729	5/8
25731	3/4

High-impact plastic storage/ carrying case with room to store above tools, and space to store additional T-nuts for other size mills.

SPECIAL SCREWS AND T-NUTS FOR MONO-BLOC AND MONO-BLOC CHAIN CLAMP

(Order one screw and one nut per Mono-Bloc)

INDIVIDUAL MONO-BLOC ITEMS

Part Number	Description
25705	Standard-Duty Mono-Bloc Clamp with 2 5/8" Arm (Includes T-wrench)
25710	Standard-Duty Riser Block
25515	Replacement Swivel Shoe
25720	T-Wrench for Standard-Duty Mono-Bloc
25540	Extension Arm
25310	Worm Gear

Part Number	Description
25730	M10x35mm Screw for 9/16 T-Nut
25733	M10x40mm Screw for 5/8 & 3/4 T-Nut
25736	M10x45mm Screw for 13/16 & 7/8 T-Nut
25747	1/2xM10 T-Nut (12mm)
25748	9/16xM10 T-Nut (14mm)
25751	5/8xM10 T-Nut (16mm)
25754	3/4xM10 T-Nut (18mm)
25757	13/16xM10 T-Nut (20mm)
25760	7/8xM10 T-Nut (22mm)

Mono-Bloc Chain Clamp



Application with large cylindrical piece.

The Mono-Bloc Chain Clamp is a simple and rapid workholding solution for a wide array of applications.

The Chain Clamp offers fast and powerful clamping with forces to 3,600 lbs. (16000N).

Additional lengths of chain can be added for large applications.



Part Number	Description
25040*	Mono-Bloc Chain Clamp with Master Link, 5 Protective Clips, Anchor, Key and 1 Meter of Chain
25041	Master Link
25042	Extra Chain (1 meter)
25043	Anchor
25045	Protective Clips (5/pk)
25720	Wrench

*Includes (2) M10 mounting screws for anchor and clamp.

T-nuts sold separately - see above.



To prevent marring or scratching on delicate pieces use the protective chain clips. (25045) Minimum radius 6"