

MILLSTACKER PREMIUM 20/35

- ✓ For milling
- √ High capacity for workpieces up to 300 mm
- ▼ Easily moved from one CNC machine to another
- ✓ Set up in less than 5 minutes
- ▼ Preparing new batch while robot is running



FEATURES

Rigid industrial construction	✓
Rotating loading table	→
Full enclosure and protection	✓
Movable	by pallet truck
Placed on 3-point self-centering anchors	✓
Fanuc 6-axis robot arm	20 / 35 kg
Drip tray for leaking coolant	✓
Workpiece side-gripping station	Option
Workpiece turn-around station for two-sided	
machining	Option
Status light	Option
Standard robot-machine interface for every	
CNC machine	✓
HALTER SmartControl Intuitive and graphical programming in 12 steps	~
Touch screen	15 inch
Free choice of pre-installed language	✓
Input can be entered in inches or mm	
Software analysis for machine utilization	_
Automatic program storage	_ ~
Max. number of CNC machines to connect with	4

HALTER SmartControl standard functionalities	
Positioning workpiece in machine vise with	
soft push function	✓
Workpiece turn-around function for two-sided	
machining	✓
Workpiece regripping for accurate positioning	✓
Inside and outside gripping	✓
Adjusting airblow distance	✓
Working with spindle orientation of the	
CNC machine	✓
Eccentric loading and unloading	✓
Robot park positioning button	✓

HALIER SmartControl enables the following optional functionalities	
Unloading workpiece on pallet	Option
Unloading workpiece on external fixed position,	
e.g. conveyor belt	Option
Unloading of residual material	Option
Cleaning of workpiece outside the CNC machine	Option
Positioning workpiece on measuring station	Option
Removal of rejected workpieces	Option
Workpiece side-gripping	Option
Customer-specific functionalities	On request

MILLSTACKER PREMIUM 20/35

Grippers

2-finger gripper for rectangular workpieces	✓
Separate grippers for raw and machined workpieces	✓
Airblow system	✓
Workpiece detection system by open/close	✓
message	✓
Quickly adjustable gripper fingers	✓
Workpiece-specific gripper fingers	Option
Pressure sensor on the robot arm monitors	
air pressure	✓

Safety

Sarety	
In-machine-space function	✓
Fanuc DCS area in combination with the Sick	
floor scanner	✓
Sliding door provided with safety sensors	✓
Standard safety fence between CNC machine and	
the Halter	✓
Autom. servo-driven door opener with integrated	
safety mechanism	Option
Closed safety circuit	✓

Input

Voltage	400 V
Peak consumption	16 A
Compressed air pressure	6 bar

Dimensions

Length	1750 mm
Width	1434 mm
Height	2220 mm
Total weight	1210 kg / 1220 kg

Capacity

Minimum workpiece (L x W)	40 mm x 40 mm
Maximum square workpiece (L x W)	180 mm x 180 mm
Maximum rectangle workpiece (L x W)	80 mm x 300 mm
Maximum height of workpiece	175 mm
Maximum load capacity robot arm	20 kg / 35 kg
Maximum total weight on rotating table	1250 kg
Maximum stacking height	350 mm
Number of stacking stations (1 empty)	12
Maximum weight per station	115 kg
Max. number of workpieces at workpiece height of 10 mm	385
Max. number of workpieces at workpiece height of 20 mm	187
Max. number of workpieces at workpiece height of 50 mm	77
Max. number of workpieces at workpiece height of 70 mm	55
Max. number of workpieces at workpiece height of 85 mm	44
Max. number of workpieces at workpiece height of 110 mm	33
Max. number of workpieces at workpiece height of 150 mm	22

BENEFITS

The HALTER LoadAssistant offers enormous advantages for your business. The experience from the users of the HALTER LoadAssistant shows us that this investment can be repaid very quickly (6-18 months).

- ✓ You realize extra output because the actual spindle hours no longer exclusively depend on the regular working hours. Also within regular working hours you realize more output, because the robot has no breaks or downtime.
- You can better respond to small or unexpected orders, because of the quick set-up time of the CNC robot cell and because it can also be run outside regular working hours.
- Decrease of hourly production costs, because the labor costs of an operator are 5 to 8 times higher than the depreciation costs of the HALTER LoadAssistant robot cell.

WORKPIECE-SPECIFIC SOLUTIONS

Halter's application engineering team can design grid plates and special gripper fingers for your specific workpieces.















T +31 88 015 74 00 • info@haltercnc.com

HALTER PORTFOLIO



The solutions that we offer ensure you can automate the production of a wide variety of workpieces. Discover our models and the different types below.

UNIVERSAL



COMPACT 12 TURNING/MILLING

- ✓ Long shafts option
- ✓ Smallest footprint
- ✓ Easily moved from one CNC machine to another



PREMIUM 20/35 TURNING/MILLING

- ✓ Most versatile system on the market
- ✓ Easily moved from one CNC machine to another
- ✓ Set up in less than 5 minutes

L
The state of the s
Wakuna 3
HALTER CO.

BIG 35/70 TURNING/MILLING

- √ Long shafts option
- √ For loading heavy workpieces
- √ High capacity for workpieces with bigger dimensions

Payload 12 kg	Payload 20 kg / 35 kg	Payload 35 kg / 70 kg
Max. workpiece size	Max. workpiece size	Max. workpiece size
135 mm x 135 mm	270 mm x 270 mm	300 mm x 300 mm
Ø 135 mm	Ø 270 mm	Ø 300 mm
Max. workpiece length	Max. workpiece length	Max. workpiece length
150 mm	250 mm	300 mm
Optional workpiece length	Optional workpiece length	Optional workpiece length
(long shafts) 250 mm	(long shafts) 450 mm	(long shafts) 800 mm

TURNSTACKER



COMPACT 12 **TURNING**

- √ High capacity for diameters up to 160 mm
- ✓ Smallest footprint
- ✓ Easily moved from one CNC machine to another




PREMIUM 20/35 TURNING

- √ High capacity for diameters up to 230 mm
- ✓ Easily moved from one CNC machine to another



BIG 35/70 **TURNING**

- √ For loading heavy workpieces
- √ High capacity for diameters up to 300 mm



MILLSTACKER



COMPACT 12

to another

MILLING

MILLING

- √ High capacity for workpieces up to 200 mm 300 mm
- ✓ Smallest footprint ✓ Fasily moved from. one CNC machine



PREMIUM 20/35

- ✓ High capacity for workpieces up to
- ✓ Easily moved from one CNC machine to another



BIG 35/70 MILLING

- √ For loading heavy workpieces
- ✓ High capacity for workpieces up to 400 mm

Payload	Payload	Payload
12 kg	20 kg / 35 kg	35 kg / 70 kg
Max. workpiece size	Max. workpiece size	Max. workpiece size
125 mm x 125 mm	180 mm x 180 mm	250 mm x 250 mm
50 mm x 200 mm	80 mm x 300 mm	100 mm x 400 mm
Max. workpiece length	Max. workpiece length	Max. workpiece length
175 mm	175 mm	225 mm